

DESCRIPTION

A specialised formula that prepares new and unseasoned timber for coating, or removes old oil coatings from existing timber. Removes tannins, mill glaze and oils.

Follow up with Equisol Vitalise to neutralise and brighten timber, ready for coating.

USES	
Suitable for	Suitable for new exterior timber including decking, pergolas, garden furniture, fences, gates, weather boards, trims and soffits.
Not suitable for	Interior use. Stripping paint or polyurethane film coatings from timber.

PROPERTIES				
Features	High strength concentrate	Coverage	 4m²/L when diluted with water Final result dependent on timber species and condition. 	
Mix ratio	Mix ONE part Equisol Prime with FOUR parts water	Clean up	Clean water	
VOC g/l	Not available	Poison Schedule	6	

APPLICATION	
Surface preparation	 Sweep deck and wash down with water. Protect areas not to be cleaned. Mask painted areas, as Prime will damage paint. May also be corrosive to metals. If mould is present use Equisol Null before using Equisol Prime.
Application	 Wear protective gloves and goggles. Mix ONE part Equisol Prime with FOUR parts water in a clean plastic container and stir thoroughly. Apply mixture to timber with stiff bristle brush and scrub lightly to ensure good penetration. Leave for about 20 mins, taking care to keep timber wet. Do not allow surface to dry. Rinse mixture off thoroughly with a high pressure water cleaner. Allow to dry before coating. Repeat as spot remover on remaining dark patches or stubborn stains.



SAFETY DIRECTIONS Harmful if swallowed and in contact with skin. Safety Causes allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life. precautions • Avoid breathing mist, vapours or spray. Wear protective clothing, gloves, eye/face protection and suitable respirator as required. Wash hands, face and all exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated clothing should not be allowed out of the workplace, and should be washed before re-use. **Protective** Wear safety shoes, overalls, gloves, chemical goggles equipment Health effects See Safety Data Sheet for additional information. • FIRST AID: If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 13 11 26; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand. • **SWALLOWED:** If swallowed, rinse mouth. Do NOT induce vomiting. Give a glass of water. Immediately call a POISON CENTRE or doctor. • EYE: Hold eyes open, flush with running water for at least 15 minutes and see a doctor. • SKIN: If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. • INHALED: Remove from contaminated area - avoid becoming a casualty. Allow patient most comfortable position and keep warm. Apply artificial respiration if not breathing. Seek medical advice. **Flammability** Non-flammable Fire Suppression Not combustible If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder). • Avoid breathing product of combustion. **Spills** • Clear area of all unprotected personnel. Slippery when spilt. Wear protective equipment. Absorb with sand or soil. Collect and seal in properly labeled drums. Dispose of contents/ containers in accordance with local regulations. Storage Keep out of reach of children. • Store in a closed container, in a well ventilated place and away from oxidizing agents and foodstuffs. Disposal • Do NOT pour leftover product down the drain. • Keep unwanted product in sealed containers for disposal via chemical waste collections in accordance with local, regional, national and international regulations.

For full safety information see Prime Safety Data Sheet

Final result and level of protection is dependent on many variables including exact timber species, colour, timber age, preparation, degree of weathering, correct application, climate and exposure. Information contained herein is correct at time of printing and is intended as a guide only. It is your responsibility to verify accuracy of all information and seek professional advice where necessary. If in doubt of result, a timber sample should be treated first. Equisol makes no representations or warranties of any kind with respect to this guide or its contents and will not, under any circumstances, be liable for any injury, loss or damage arising out of or related to the use of information in this guide. Equisol is manufactured under licence for Surface Logic Pty Ltd.

PRIME TECHNICAL DATA SHEET ISSUE 2. SEPTEMBER 2021



HANDLING AND STORAGE		
Handling	Avoid skin and eye contact and inhalation of vapour, mist or aerosols.	
Storage	Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from strong acids and oxidising agents. Store away from sources of heat and/or ignition.	
	Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.	
	This material is a Scheduled Poison Schedule 6 (Poison) and must be stored, maintained and used in accordance with the relevant regulations.	

TRANSPORT		
Road and Rail Transport	Not classified as Dangerous Goods by the criteria of the Australian Code for the Transport of Dangerous Goods by Road & Rail and the New Zealand NZS5433: Transport of Dangerous Goods on Land.	
Marine Transport	Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.	
Air Transport	Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.	